

## The industry standard for beverage carton packaging.

Strong and sustainable, the recyclable CarrierKote® paperboard maintains integrity in wet and cold environments. With crisp, vibrant graphics thanks to its proprietary clay coating and outstanding converting performance in the areas of die-cutting, folding and gluing, it's no wonder CarrierKote is the industry standard for beverage carton packaging.

### Features

- Engineered for strength
- Proprietary clay coating with a smooth, opaque surface for printing and embellishment options
- Outstanding converting performance in the areas of die-cutting, folding and gluing
- Produced at a single mill

### Benefits

- Maintains strength and integrity in wet and cold environments
- Offers excellent tear strength in a variety of environments throughout the supply chain
- Offers exceptional printability with crisp, vibrant graphics
- Delivers consistent composition and quality
- Can help meet corporate sustainability goals
- Provides packaging design flexibility with options such as handles, windows, and apertures

## Additional product information

### Sustainability

- Made with up to 15% recycled fibre.
- Recyclable.
- 100% PEFC Certified - BMT-PEFC-COC-0332. Contact your Smurfit Westrock sales representative for certified fibre availability for this product.

### Quality

- Produced at an ISO 9001 certified facility.

### Environmental and Product Safety

- Notices under US California Proposition 65 and the EU REACH regulation are not required.
- Meets heavy metal limits of the US Model Toxics in Packaging rules and Article 11 of EU Directive 94/62/EC.

### Food Contact

- Contact your sales representative for information on specific markets and end uses.

### Applications

- Beverage
- Filter frames

### Product classification

- Coated Natural Kraft™
- CNK® Paperboard
- Coated Unbleached Kraft

### Region

- EMEA (Europe, the Middle East and Africa)

Grade availability (EMEA) and typical board properties

Grade availability												Units	Method	
Nominal basis weight		320	350	380	400	415	430	445	465	480	500	515	gsm	T-410
Caliper (pts)		0.016	0.018	0.020	0.021	0.022	0.023	0.024	0.025	0.026	0.027	0.028	inches	T-411
Thickness		406	457	508	533	559	584	610	635	660	686	711	microns	T-411
Moisture content		7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	percent	T-412
ZDT		241	241	241	241	241	241	241	241	241	241	241	kPa	T-541
Elmendorf Tear														
Dry	MD	430	490	555	585	600	630	655	680	720	750	785	gf	T-414
	CD	475	540	595	630	650	680	705	735	765	825	850	gf	T-414
Wet	MD	400	450	500	530	570	575	600	630	655	680	700	gf	
	CD	425	504	548	570	600	615	630	655	675	715	730	gf	
Stiffness														
Taber 15°	MD	18.7	25.2	32.7	36.9	41.2	45.9	50.8	55.9	61.4	67.0	73.0	mNm	T-489
	CD	8.5	11.3	14.8	16.8	19.0	21.4	23.9	26.7	29.6	32.8	36.0	mNm	T-489
Smoothness														
Sheffield		150	150	150	150	150	150	150	150	150	150	150	SU	T-538
Coated side														
Parker Print		2	2	2	2	2	2	2	2	2	2	2	µm	T-555
GE Brightness		74	74	74	74	74	74	74	74	74	74	74	percent	T-452
Colour														
Hunter	b	-2.6	-2.6	-2.6	-2.6	-2.6	-2.6	-2.6	-2.6	-2.6	-2.6	-2.6	L-a-b	T-524

Values are subject to change without notice.

For more information, please contact your Smurfit Westrock representative or visit our website at [westrock.com/carrierkote](https://westrock.com/carrierkote).

The information contained in this Product Guide is accurate to the best of Smurfit Westrock's knowledge and belief. It is intended, however, only as an introduction to the typical properties of the product. Smurfit Westrock disclaims any guarantee or warranty with respect to the accuracy of this information or, based on this document, with respect to the suitability of the product for any particular use, including, but not limited to, the compliance of the product with laws, regulations, or standards. This information is subject to change without notice.

All Smurfit Westrock North American mills are ISO registered and certified to the SFI®, PEFC/29-31-216, and FSC® C104002 Chain of Custody Standards. SFI marks are registered marks owned by the Sustainable Forestry Initiative Inc.

